

SUPAPA DE RETINERE CU CLAPA Ref. 364/365

Ref. : DS 364

Rev. : 5

Date : 11/08

Page 1/1



Valves and fittings

90 rue du ruisseau 38297 ST QUENTIN FALLAVIER
Tel:(33)04.74.94.15.90 Fax:(33)04.74.95.62.08
E.mail : sferaco@sferaco.fr

SPECIFICATII :

- . Tip clapeta retinere
- . Intre flanse GN10/16

MOD DE FOLOSINTA :

- . Pentru fluide comune
- . Temperatura max. : 100°C for 364
- . Temperatura max. : 200°C for 365
- . Presiune max. : 16 bars up to DN200 (10 bars over)
- . A nu se folosii in debit pulsatoriu
- . Numai pentru montaj vertical sau orizontal
- . Viteza max.: 3 M. / Sec.

GAMA :

- . Intre flanse GN10/16 otel carbonic **Ref. 364** DN40 to DN300
- . Intre flanse GN10/16 otel inox **Ref. 365** DN40 to DN300

MATERIAL :

DENUMIRE	MATERIAL 364	MATERIAL 365
Corp	Otel carbon	Otel inox 316
Disc	Otel carbon	Otel inox 316
Garnitura	NBR	Viton

DIMENSIUNI :

	DN	40	50	65	80	100	125	150	200	250	300
Ref.	D	93	109	129	144	164	194	220	275	330	380
364	A	80	89	111	119	147	171	200	256	302	352
365	B	21	32	40	51,3	70	86	105	148	181	234
	E	14	14	14	14	18	18	20	22	26	28
Weig.		0,63	0,84	1,16	1,53	2,34	3,14	3,98	6,6	11,54	24

DIMENSIUNI GARNITURA :

	DN	40	50	65	80	100	125	150	200	250	300
Ref.	D4	26,7	37,2	44	58,2	75	94,2	116	156,2	193,5	242
364	d4	3	3	3	4	4	5	5	6	6	7
Ref.	D4	26,5	37,2	44	57,3	75	93,5	114,8	155	193	240,5
365	d4	3	3	3	4	4	5	5	6	6	7
Ref.	D2	71	87,5	98,5	118,5	135,5	160	187	239	287	337
364/365	d2	4	3,5	3,5	3,5	3,5	5	5	5	6	6

STANDARD :

. 364 EXCLUS DE LA DIRECTIVE 97/23/CE CE N°0035
Categoria de risc II for Ref. 365

SFAT : Staturile si recomandarile noastre nu garanteaza iar SFERACO nu este responsabil pentru daune. Clientul are obligativitatea de a verifica compatibilitatea produselor cu conditiile reale de utilizare.

