



Fittings with TYTON or screw socket

For socket fittings, highest quality, especially in the socket area, is crucial to avoid installation errors and ensure the secure seating of the seal. Choose manufacturers that offer the most comprehensive product range possible.

Recommendations for your tenders:

- Frischhut brand or equivalent
- Material according to DIN EN 545
- Corrosion protection by epoxy resin powder coating with BPA-reduced powder (R8) inside and outside according to quality assurance RAL-GZ 662 – GSK
- Certification for drinking water
- External monitoring by accredited, neutral testing institute
- Cast-on marking „FGR“ including membership number as proof of manufacturer



EN-TYTON
hydrant duckfoot bend 90°



EU-TYTON
flanged socket



MMA-TYTON
double-socket T
with flanged branch



MMB-TYTON
double-socket T
with socket branch



MMK-TYTON 11° 22° 30° 45°
double-socket bend



MMQ-TYTON
double-socket elbow



MMR-TYTON
double-socket reducer



MK-TYTON 11° 22° 30° 45°
socket bend



MQ-TYTON
socket elbow



**Anchoring clamp
type M**
for TYTON- and screw
socket Union



EU-screw socket
flanged socket



U-screw socket
double sliding socket



**Anchoring clamp
type SM**
for screw socket connections